

Winter Cover for ERIBA TOURING

Protect your vehicle from ice, snow and dirt

This 3-part vehicle cover is a perfect fit for ERIBA TOURING Troll, Triton and Familia caravan models.

It consists of a 2-part cover, that is pulled into the piping rail that runs around the vehicle using sewn-on 7 mm piping, and a roof protection canvas, that is secured using the three lashing straps provided. Two integrated zips make it possible to open the entrance door when the cover is fitted.



Material: SFS-3 non-woven material 160 gr/m², breathable, water-repellent, UV-stabilised

Care instructions:

If the insulation becomes dirty, the non-woven material can be cleaned with a damp cloth and, if necessary, a small amount of detergent.

Assembly instructions:

Step 1: 2-part cover



- Lay out the first half of the vehicle cover (with two zips for door opening) next to the vehicle on the driver side.
- Then use the sewn-on piping to pull the cover into the piping rail that runs around the vehicle and pull it round the front to the passenger side.
IMPORTANT: ONLY pull on the piping trim of the cover! Not the material!
- Use the four openings on the piping rail to ensure that the piping remains in the rails.



- The second half is pulled round the vehicle from the back right, round the rear to the driver side.
- When both halves are pulled round, ensure that each half begins and ends at the middle of the vehicle at the front and back



- Use the elastic strap sewn into the bottom edge to secure the cover to the bottom edge of the vehicle. This ensures that it is sealed from below.
- Before the front velcro is fastened, the supplied elastic straps should be fed under the drawbar and fitted in the relevant eyelets.
- Then the two halves can be connected together using the velcro strip.



Step 2: Roof protection canvas

- Pull the roof protection canvas over the roof.
- Ensure that the canvas does not get caught on the chimney.
- To aid correct positioning, the front of the roof protection canvas has a blue arrow.



Step 3: Straps

- Attach two straps to the blue eyelet band that is sewn onto the roof protection canvas and pass them under the vehicle to the other side.
- A third strap is fitted at the front around the drawbar.

